

# FS24LCSS



20" x 18.75" x 17.75" (H x W x D)

Compact all-freezer for general purpose use, manual defrost with lock and stainless steel exterior

### Highlights:

Compact "cube" size is ideal for use on top of counters

Stainless steel wrapped exterior

Factory installed lock provides security you can count on

### Product Features:

Compact size	Convenient "cube" shape is ideal for use on top of counters
Stainless steel wrapped exterior	Door and cabinet are fully wrapped in 304 grade stainless steel for lasting durability
Factory installed lock	Keyed lock for a secure interior
Manual defrost	Static cooling system
One-piece interior liner	Seamless interior for easier cleanup
Removable shelf	Includes one wire shelf for easier storage
Reversible door	User reversible door swing for added flexibility
Adjustable thermostat	Dial thermostat for easy temperature management
Flat door liner	Designed to comply with CDC guidelines

## FS24LCSS Specifications:

Overview	
Height of Cabinet	19.75" (50 cm)
Height to Hinge Cap	20.0" (51 cm)
Width	18.75" (48 cm)
Depth	17.75" (45 cm)
Depth with Handle	18.5" (47 cm)
Depth with door at 90°	34.75" (88 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	41.0 lbs. (19 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101049090
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	14.38" (37 cm)
Interior Width	13.5" (34 cm)
Interior Depth	13.25" (34 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
High Side PSI	110.0
Low Side PSI	70.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	13.5" (34 cm)
Compressor Step Depth	6.0" (15 cm)

